

Technical Specification:

Model	SBRPM - 6/6	SBRPM - 8/8	SBRPM - 16/8
Output / Hout (bottles)*	2500 to 7500	4000 to 10000	7000 to 14500
No. of Head/Syringe	6	8	8
No. of Head/Syringe	6	8	16
Fill Size***	30 ml to 1000 ml		
Electric Specification	Main Machine	3 HP / 415 Volts / 50 Hz.	5 HP / 415 Volts / 50 Hz.
	Oriental Bowl	0.25 Hp / 415 Volts / 50 Hz.	0.5 Hp / 415 Volts / 50 Hz.
	Conveyor	0.5 Hp / 415 Volts / 50 Hz.	0.75 Hp / 415 Volts / 50 Hz.
Height of Conveyor**	910 mm to 960 Adjustable		
Machine Dimensions** (In mm) L x W x H	3050 x 1400 x 2200		3660 x 1700 x 2400
Net Weight	2500 Kgs.	2650 Kgs.	4200 Kgs.
Change Parts Required	(A) Container: Star Wheel, Back guide, Feed Worm, Nozzle (B) Cap: Die, Delivery Chute, Bowl (C) Syringes (If volume higher/lower then above specification)		

Input Specification:

ROPP / Screw Cap Specification	Diameter**	19 mm to 38 mm**
	Height **	15 to 18.3 mm
Container Size**	Round Shape	Respectively height 58 mm to 240 mm*** (Height option for other bottle height available)
	Flat / Square	15 mm to 100 mm (Length)*** Respectively 10 mm to 50 mm (Width)*** Respectively height 58 mm X 240 mm*** (Height Option for other bottle height available)

Depends on bottle size, cap size and type of cap.

** We can supply as per customer requirements.

*** With help change parts.